
HSM

Series

Low Lift Safety Valve - Bronze Type

- Size: 1/2"(DN13) to 2"(DN50)
- Working Pressure: 0.3 to 25 bar
- Working Temp.: -45°C to 185°C
- Connection Standard: NPT/PT/BSPP/BSPT.....etc.



HSL

Series

Low Lift Safety Valve - Close Bonnet

- Size: 1"(DN25) to 6"(DN150)
- Working Pressure: 0.3 to 20 bar
- Working Temp.: -5°C to 300°C
- Connection Standard: ANSI/JIS/PN.....etc.



HSD

series

Low Lift Safety Valve - Open Bonnet

- Size: 1"(DN25) to 8"(DN200)
- Working Pressure: 0.3 to 40 bar
- Working Temp.: -29°C to 350°C
- Connection Standard: ANSI/JIS/PN.....etc.



HSR

series

High Lift Safety Valve -Bronze Type

- Size: 1/2"(DN15) to 2 1/2"(DN65)
- Working Pressure: 0.1 to 40 bar
- Working Temp.: -185°C to 200°C
- Connection Standard: NPT/PT/BSPP/BSPT....etc.



HSY

series

High Lift Safety Valve -Stainless Steel Type

- Size: 1/2"(DN15) to 1 1/2"(DN40)
- Working Pressure: 0.1 to 50 bar
- Working Temp.: -196°C to 350°C
- Connection Standard: NPT/PT/BSPP/BSPT.....etc.



HST

series

High Lift Safety Valve - High Pressure

- Size: 1/2"(DN15) to 2"(DN50)
- Working Pressure: 0.1 to 110 bar
- Working Temp.: -196°C to 350°C
- Connection Standard:
NPT/PT/BSPP/BSPT/ANSI/JIS/PN.....etc



HSK

series

Full Bore Safety Valve

- Size: 1"(DN25) to 6"(DN150)
- Working Pressure: 0.3 to 40 bar
- Working Temp.: -5°C to 300°C
- Connection Standard: ANSI/JIS/PN.....etc.



HSU

series

Full Bore Safety Valve - High Pressure

- Size: 1/2"(DN15) to 2"(DN50)
- Working Pressure: 0.1 to 110 bar
- Working Temp.: -196°C to 350°C
- Connection Standard:
NPT/PT/BSPP/BSPT/ANSI/JIS/PN.....etc

